



SELF-PRIMING CENTRIFUGAL PUMPS - CNH Series CNH

The CNH series is made up of single-stage centrifugal pumps with self-priming device, axial suction port, open centrifugal impeller and independent shaft.

The self-priming devices is made up of a helical rotor installed in front of the impeller and a rotor chamber which is off-centre in relation to the axis of the centrifugal stage.

The series is made up of range of 2 models with open impeller, independent shaft and standard IEC motor. Mixed construction: pressed/cast stainless steel - AISI 316L (1.4404) - CF3M (1.4409).

Investment casting and electrochemical polishing treatment guarantee excellent levels of surface finish.



The pump incorporates a self-priming device which gives the centrifugal pump its suction capacity; this component guarantees continuous pump operation in applications handling biphasic fluids.

CNH self-priming centrifugal pumps can be used in industrial applications, for example in the food, dairy and beverage sectors, for tank emptying operations, CIP solution recirculation and for handling liquids with a high air content.



Close-coupled construction made entirely from stainless steel with standard motor, shaft with compression locking, internal seal and open impeller based on CN series pumps.

The clamp casing and seal design allows quick disassembly for inspection, cleaning and maintenance. Protective motor shroud. Series of pumps available in two different versions of liquid recirculation: Version with drainage feature guarantees complete emptying of the pump; Version without drainage.



Investment cast double vane rotor for creating the liquid ring inside the front section of the pump body.



Open reverse vane impeller with increased dimensions, designed in accordance with performance optimization criteria.

TECHNICAL DATA

Flow rate up to 65 m³/h Head values up to 55 m Maximum suction pressure 4 bar (PN 10) Temperature range: -10°C to +120°C

Seals:


Hygienic mechanical seals with seat standardized to EN 12756, ISO 3069 standards


Seal materials (FDA, Regulation (EC) No. 1935/2004): EPDM Fluorocarbon P.T.F.E. (Fep)

Connections:

DIN - SMS - IDF - BS / RJT - DS - CLAMP and EN 1092-1 PN 16 flanges and, on request, available in compliance with international standards.








Dimensions not binding - DN = DIN 11851 female connection with standard IEC/EN motors

	Pump type	IEC motor dimensions:	DNa	DNm	A	в	с	D	Е	E'	G	н	к	K'	I	J	J'	L	v
ſ	CNH 2	112	65	50	142	314	189	315	230	180	108	205	666	749	200	405	445	369	195
		132 S				293		400	279	279		230	702	818		430	470	380	220
		132 M										230	740	010					
Γ	CNH 3	132 S	80	65	164,5	314	188	400	216	216	129	230	723	840	255	455	470	380	217
		132 M				314	100	400					761	040					
L		160				301	218	475	270	333		280	867	998		485	597	473	267



cod. DCATLCNHGB 03/20

C.S.F. Inox S.p.A. Strada per Bibbiano, 7 - 42027 Montecchio E. (RE) - ITALY EU Ph +39.0522.869911 r.a. - Fx +39.0522.865454 - italia@csf.it - www.csf.it

NCSF Export Department • Commercial Étranger • Comercial Extranjero

All the instructions, data and representations (in whatever way executed) listed in this publication are indicative and do not binding. C.S.F. does not stand surety or undertake any obligation for the utilisation of this document and for the information contained. In particular, it does not guarantee against omissions or errors of the data and drawings here indicated. Notice that the technical specifications, information and representations in this document are merely indicative and approximate. C.S.F. INOX reserves the right at any moment and without notice to modify the data, drawings and information indica-ted in this document.

Ph +39.0522.869922 - Fx +39.0522.869841 - export@csf.it - www.csf.it